Trade name: P 2 1 L

Version: 8 / GB

Replaces Version: 7 / GB



Substance number: 3514009700019

Date revised: 27.06.2024

Print date: 22.10.2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

P 2 1 L

-

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Industrial uses: Screen and pad printing auxiliary

#### Uses advised against

Use by consumers (private households), as the necessary technical measures and personal protective equipment are not available to private households.

#### 1.3. Details of the supplier of the safety data sheet

#### Address/Manufacturer

Marabu GmbH & Co. H Asperger Strasse 4 71732 Tamm Deutschland	<g< th=""></g<>
Telephone no.	+49-7141/691-0
Information provided by / telephone	Department product safety
E-mail address of person responsible for this SDS	PRSI@marabu.com
Information provided by / telephone	Department product safety
E-mail address of person responsible for this SDS	PRSI@marabu.com

#### **1.4. Emergency telephone number**

(+49) (0)621-60-43333

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

# Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)

· · ·	
Flam. Liq. 3	H226
Acute Tox. 4	H332
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H335
STOT RE 2	H373
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

Version: 8 / GB



Substance number: 3514009700019

Replaces Version: 7 / GB

Date revised: 27.06.2024 Print date: 22.10.2024

### 2.2. Label elements

### Labelling according to regulation (EC) No 1272/2008

Hazard pictograms



#### Signal word

Danger

#### Hazard statements

H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H304	May be fatal if swallowed and enters airways.
H412	Harmful to aquatic life with long lasting effects.

#### **Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260.8	Do not breathe vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P331	Do NOT induce vomiting.

#### Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains

Ethyl benzene; Xylene

#### 2.3. Other hazards

No special hazards have to be mentioned.

The product contains no PBT substances. The product contains no vPvB substances. This product does not contain a substance that has endocrine disrupting properties with respect to human. The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### Hazardous ingredients

Xylene					
CAS No.	1330-20-7				
EINECS no.	215-535-7				
Registration no.	01-2119488	216-32/0	)1-2119486	6136-34	
Concentration	>=	50	<	92	%

Safety data sheet in acc	ordance with	n regulation (EC) N	o 1907/:	2006			
Trade name: P 2 1 L						_	Marabu
		Version: 8 / GB				Date revised: 27.06.2	:024
Substance number: 35140	009700019	Replaces Version	: 7 / GB			Print date: 22.10.202	4
Classification (	Regulation (E	C) No. 1272/2008)					
	Skin	Irrit. 2	H315				
	Flam	n. Liq. 3	H226				
	Acut	e Tox. 4	H332				
	Acut	e Tox. 4	H312				
	Eye	Irrit. 2	H319				
	STO	T SE 3	H335				
	STO	T RE 2	H373				
	Asp.	Tox. 1	H304				
	Aqua	atic Chronic 3	H412				
cATpE	inhalative,	Dust/Mist	1,5		mg/l		
Ethyl benzene							
CAS No.	100-	41-4					
EINECS no.	202-	849-4					
Registration no	o. 01-2	119489370-35					
Concentration		>= 10	<	25		%	
Classification (	Regulation (E	EC) No. 1272/2008)					
	Flam	n. Liq. 2	H225				
	Acut	e Tox. 4	H332				
	STO	T RE 2	H373				
	Asp.	Tox. 1	H304				
	Aqua	atic Chronic 3	H412				
сАТрЕ	inhalative,	Dust/Mist	1,5		mg/l		
cATpE	inhalative,		11		mg/l		

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

# **General information**

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

# After inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

# After skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.

# After eye contact

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.


# After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

# Adhere to personal protective measures when giving first aid

Use personal protective equipment in case of possible contact with the product (see section 8).

Version: 8 / GB



Substance number: 3514009700019

Replaces Version: 7 / GB

Print date: 22.10.2024

### 4.2. Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11. Further symptoms are possible.

### 4.3. Indication of any immediate medical attention and special treatment needed

#### Hints for the physician / treatment

Treat symptomatically

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

Aalcohol resistant foam, CO2, powders, water spray/mist

#### Non suitable extinguishing media

water jet

#### 5.2. Special hazards arising from the substance or mixture

In the event of fire the following can be released: Carbon monoxide (CO); Carbon dioxide (CO2); dense black smoke; Hydrogen chloride (HCI); Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.

#### 5.3. Advice for firefighters

#### Special protective equipment for fire-fighting

Use self-contained breathing apparatus. Wear full chemical protective clothing. Fire fighter's clothing must conform to European standard EN469.

#### Other information

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Keep away sources of ignition. Remove persons to safety. Ensure adequate ventilation. Keep away unprotected persons. Avoid contact with skin, eyes and clothing. Avoid breathing vapours. For emergency responders: Wear personal protective equipment. Use breathing apparatus if exposed to vapours/dust/aerosol.

#### 6.2. Environmental precautions

Do not allow to enter drains or waterways. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

#### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent - avoid use of solvents.

#### 6.4. Reference to other sections

Information regarding personal protective measures, see Section 8. Information regarding waste disposal, see Section 13.

Version: 8 / GB



Substance number: 3514009700019

Replaces Version: 7 / GB

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

#### Advice on safe handling

Due to the organic solvents' content of the mixture: Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Isolate from sources of heat, sparks and open flame. No sparking tools should be used. Avoid skin and eye contact. Avoid the inhalation of particulates and spray mist arising from the application of this mixture. Smoking, eating and drinking shall be prohibited in application area. For personal protection see Section 8. Never use pressure to empty: container is not a pressure vessel. Always keep in containers of same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or water courses.

#### Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

#### Classification of fires / temperature class / Ignition group / Dust explosion class

Classification of fires B (Combustible liquid substances) Temperature class T2

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Store in accordance with national regulation

#### Hints on storage assembly

Store away from oxidising agents, from strongly alkaline and strongly acid materials.

#### Further information on storage conditions

Observe label precautions. Store between 15 and 30 °C in a dry, well ventilated place away from sources of heat and direct sunlight. If the storage conditions are not observed, the minimum shelf life is no longer guaranteed. Due to the organic solvents' content of the mixture: Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### 7.3. Specific end use(s)

Screen and pad printing auxiliary

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Exposure limit values

Ethyl benzene				
List	EH40			
Туре	WEL			
Value	441	mg/m³	100	ppm(V)
Short term exposure limit	552	mg/m³	125	ppm(V)
Skin resorption / sensibilisation	on: Sk2011			

Trade name: P 2 1 L					м
	Version: 8	/ GB	Dat	te revised: 27.06.2024	
Substance number: 3514009700019	019 Replaces Version: 7 / GB		Prin	t date: 22.10.2024	
Ethyl benzene					
List	EU				
Value	442	mg/m³	100	ppm(V)	
Short term exposure limit	884	mg/m³	200	ppm(V)	
Skin resorption / sensibilisation	on: SkinRer	narks: 2000/39/EG			
Xylene					
List	EH40				
Туре	WEL				
Value	220	mg/m³	50	ppm(V)	
Short term exposure limit	441	mg/m <sup>3</sup>	100	ppm(V)	
Skin resorption / sensibilisation			100	PP(*)	
·					
Xylene	EU				
List Value	EU 221	ma/m <sup>3</sup>	50		
		mg/m³		ppm(V)	
Short term exposure limit	442	mg/m <sup>3</sup>	100	ppm(V)	
Skin resorption / sensibilisation	on: SkinRer	narks: 2000/39/EG			
Derived No/Minimal Effect I	_evels (DN	IEL/DMEL)			
Xylene					
Type of value	Derived	No Effect Level (DNI	EL)		
Reference group	Worker	•	,		
Duration of exposure	Long te				
Route of exposure	inhalati				
Mode of action	System	ic effects			
Concentration	221		mg/m³		
Type of value	Derived	No Effect Level (DNI	EL)		
Reference group	Worker				
Duration of exposure	Short te	erm			
Route of exposure	inhalati				
Mode of action	•	ic effects			
Concentration	442		mg/m³		
Type of value	Derived	No Effect Level (DNI	EL)		
Reference group	Worker				
Duration of exposure	Long te				
Route of exposure	inhalati				
Mode of action	Local e	ffects			
Concentration	221		mg/m³		
Type of value		No Effect Level (DNI	EL)		
Reference group	Worker				
Duration of exposure	Short te				
Route of exposure	inhalati				
Mode of action	Local e	ttects			
Concentration	442		mg/m³		
Type of value	Derived	No Effect Level (DN	EL)		
		Page: 6 (17)			

Frade name: P 2 1 L		
	Version: 8 / GB	Date revised: 27.06.2024
Substance number: 3514009700019	Replaces Version: 7 / GB	Print date: 22.10.2024
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	212	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	65,3	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action		
Concentration	Systemic effects	mg/m3
Concentration	260	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	65,3	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Short term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	260	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	125	mg/kg/d
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
	,	

rade name: P 2 1 L		м
	Version: 8 / GB	Date revised: 27.06.2024
Substance number: 3514009700019	Replaces Version: 7 / GB	Print date: 22.10.2024
Ethyl benzene		
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Systemic effects	
Concentration	77	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	inhalative	
Mode of action	Local effects	
Concentration	293	mg/m³
Type of value	Derived No Effect Level (DNEL)	
Reference group	Worker	
Duration of exposure	Long term	
Route of exposure	dermal	
Mode of action	Systemic effects	
Concentration	180	mg/kg/d
Tupo of voluo	Dorived No Effect Level (DNEL)	
Type of value Reference group	Derived No Effect Level (DNEL) Consumer	
Duration of exposure		
Route of exposure	Long term inhalative	
Mode of action	Systemic effects	
Concentration	15	mg/m³
Concentration	15	ing/in-
Type of value	Derived No Effect Level (DNEL)	
Reference group	Consumer	
Duration of exposure	Long term	
Route of exposure	oral	
Mode of action	Systemic effects	
Concentration	1,6	mg/kg/d
Predicted No Effect Conce	ntration (PNEC)	
Xylene		
Type of value	PNEC	
Туре	Freshwater	
Concentration	0,327	mg/l
Type of value	PNEC	
Туре	Saltwater	
Concentration	0,327	mg/l
Type of value	PNEC	

rade name: P 2 1 L		
	Version: 8 / GB	Date revised: 27.06.2024
ubstance number: 3514009700019	Replaces Version: 7 / GB	Print date: 22.10.2024
Туре	Freshwater sediment	
Concentration	12,46	mg/kg
Type of value	PNEC	
Туре	Marine sediment	
Concentration	12,46	mg/kg
	PNEC	
Type of value		
Type	Soil	
Concentration	2,31	mg/kg
Type of value	PNEC	
Туре	Sewage treatment plant (STP)	
Concentration	6,58	mg/l
Type of value	PNEC	
	Water (intermittent release)	
Type Concentration	0,327	mg/l
Concentration	0,021	iiig,i
Ethyl benzene		
Type of value	PNEC	
Туре	Freshwater	
Concentration	0,1	mg/l
Type of value	PNEC	
Туре	Saltwater	
Concentration	0,01	mg/l
	PNEC	
Type of value	Sewage treatment plant (STP)	
Type Concentration	9,6	mg/l
Concentration	9,0	ngn
Type of value	PNEC	
Туре	Freshwater sediment	
Concentration	13,7	mg/kg
Type of value	PNEC	
Туре	Marine sediment	
Concentration	1,37	mg/kg
Type of value	PNEC	
Type	Soil	
Concentration	2,68	mg/kg

# 8.2. Exposure controls

Version: 8 / GB

Date revised: 27.06.2024

Substance number: 3514009700019

Replaces Version: 7 / GB

Print date: 22.10.2024

#### Exposure controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

#### General protective and hygiene measures

Observe the usual precautions for handling chemicals. Wearing closed work clothing is required. Wash hands and / or face before breaks and after work. Take off dirty, soaked clothes immediately. Wash soiled clothing before re-use. Store work clothing separately.

#### **Respiratory protection**

If workers could be exposed to concentrations above the exposure limit they should use a respirator to EN 140, fitted with a filter suitable for both particulates and vapours, to EN 14387, with an assigned protection factor of at least 10 (e.g. A2P3) Selection of any respiratory protective equipment should ensure that it is adequate to reduce exposure to protect the worker's health and is suitable for the wearer, task and environment, including consideration of the facial features of the wearer.

#### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

Use gloves tested according to EN ISO 374.

For prolonged or repeated handling, use

Appropriate Material Butyl rubber

Material thickness	>	0,7	mm
Breakthrough time	>	480	min

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

#### Eye protection

Use safety eyewear tested according to EN ISO 16321-1 designed to protect against splash of liquids.

#### Body protection

Personnel should wear anti-static clothing made of natural fibre or of high temperature resistant synthetic fibre. Cotton or cotton/synthetic overalls or coveralls are normally suitable.

#### **Environmental exposure controls**

Do not allow to enter drains or water courses. If the legally prescribed emission limits are exceeded, a suitable exhaust air purification system must be installed.

# **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Colour	colourless
Odour	solvent-like
Malting paint	

ade name: P 2 1 L		
	Version: 8 / GB	Date revised: 27.06.2024
ubstance number: 3514009700019	Replaces Version: 7 / GB	Print date: 22.10.2024
Remarks	Not applicable due to natu	re of the product
Freezing point		
Remarks	Not applicable due to natu	re of the product
Boiling point or initial boili	ng point and boiling range	
Reference substance	Ethyl benzene	
Value	appr. 136	°C
Pressure	1.013 hPa	
Source	Literature value	
Flammability		
Flammable.		
Upper and lower explosive	limits	
Reference substance	Xylene	
Lower explosion limit	appr. 0,8	%(V)
Reference substance	Xylene	
Upper explosion limit	appr. 8	%(V)
Source	Literature value	
Flash point		
Value	30	C
Method	ASTM D 6450 (CCCFP)	
Auto-ignition temperature		
Value	appr. 430	°C
Source	Literature value	
Decomposition temperatur	e	
Remarks	No decomposition if used a	as prescribed.
pH value		
Remarks	Not applicable	
Remarks	substance/mixture is non-s	soluble (in water)
Viscosity		
kinematic		
Value	< 5	mm²/s
Temperature	20 °C	
Method	derived from dynamic visco	osity
Solubility(ies)		
Remarks	Not applicable due to natu	re of the product
Partition coefficient n-octa		
Remarks	Not applicable due to natu	re of the product
Vapour pressure		
Value	8,53	hPa
Temperature	20 °C	u
Method	calculated	
Density and/or relative den		
Value	0,870	g/cm <sup>3</sup>
Temperature	20 °C	J. J. J.

#### Trade name: P 2 1 L

Version: 8 / GB

Substance number: 3514009700019 Replaces Version: 7 / GB



Method	DIN EN ISO 2811
Relative vapour density	
Value	> 1
Source	Literature value
Particle characteristics	
Remarks	Not applicable due to nature of the product

#### 9.2. Other information

#### Other information

The physical specifications are approximate values and refer to the used safety relevant component(s).

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No hazardous reactions when stored and handled according to prescribed instructions.

#### 10.2. Chemical stability

Stable under recommended storage and handling conditions (see section 7).

#### 10.3. Possibility of hazardous reactions

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

#### 10.4. Conditions to avoid

Protect from heat/overheating. When exposed to high temperatures may produce hazardous decomposition products. Avoid high concentrations of solvent vapours. Observe the notes on ventilation (section 8).

#### 10.5. Incompatible materials

Oxidising agents, strongly alkaline substances, Strongly acidic substances

#### 10.6. Hazardous decomposition products

See chapter 5.2 (Firefighting measures - Special hazards arising from the substance or mixture). No decomposition during intended use (see section 1).

# **SECTION 11: Toxicological information**

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity				
Remarks	Based or	Based on available data, the classification criteria are not met.		
Acute dermal toxicity				
Remarks	Based or	n available da	ata, the classification criteria are not met.	
Acute dermal toxicity (C	omponents	)		
<b>Xylene</b> Species LD50	rabbit > 4	1200	mg/kg	
Acute inhalational toxici	ty			
ATE	1,5429		mg/l	
Administration/Form	Dust/Mis	t		

rade name: P 2 1 L		м
	Version: 8 / GB	Date revised: 27.06.2024
Substance number: 3514009700019	Replaces Version: 7 / GB	Print date: 22.10.2024
Method ATE	calculated value (Regulation (EC > 20	C) No. 1272/2008) mg/l
Administration/Form Method Remarks	Vapors calculated value (Regulation (EC The classification criteria are me	
Acute inhalative toxicity (	Components)	
<b>Xylene</b> Species LC50 Duration of exposure Administration/Form	rat > 29 4 h Vapors	mg/l
Skin corrosion/irritation		
evaluation Remarks	irritant The classification criteria are me	et.
Serious eye damage/irrita	tion	
evaluation Remarks	irritant The classification criteria are me	et.
Sensitization		
Remarks	Based on available data, the cla	ssification criteria are not met.
Mutagenicity		
Remarks	Based on available data, the cla	ssification criteria are not met.
Reproductive toxicity		
Remarks	Based on available data, the cla	ssification criteria are not met.
Carcinogenicity		
Remarks	Based on available data, the cla	ssification criteria are not met.
Specific Target Organ Tox	icity (STOT)	
<b>Single exposure</b> Remarks	The classification criteria are me	et.
evaluation	May cause respiratory irritation.	
Repeated exposure		
Remarks evaluation	The classification criteria are me	et. rrough prolonged or repeated exposure
Aspiration hazard	may cause damage to organs th	inough profoliged of repeated exposure
Harmful: may cause lung da The classification criteria ar	-	
11.2. Information on other h	azards perties with respect to human	<b>c</b>
Endoornie distupung prop	in the main respect to mullian	

The product does not contain a substance that has endocrine disrupting properties with respect to humans.

#### Experience in practice

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central Symptoms and signs include headache, dizziness, fatigue,

Trade name: P 2 1 L

Version: 8 / GB

Substance number: 3514009700019 Replaces Version: 7 / GB



Date revised: 27.06.2024

Print date: 22.10.2024

muscular weakness, drowsiness and in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Irritating to skin. The liquid splashed in the eyes may cause irritation and reversible damage. Ingestion may cause nausea, diarrhoea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

#### Other information

There are no data available on the mixture itself.

The mixture has been assessed following the additivity method of the CLP Regulation (EC) No 1272/2008 and classified for toxicological hazards accordingly.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

#### **General information**

There are no data available on the mixture itself.Do not allow to enter drains or water courses.The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

### 12.2. Persistence and degradability

#### **General information**

No data available

#### 12.3. Bioaccumulative potential

#### **General information**

There are no data available on the mixture itself.

#### Partition coefficient n-octanol/water (log value)

Remarks

Not applicable due to nature of the product

#### 12.4. Mobility in soil

#### **General information**

There are no data available on the mixture itself.

#### 12.5. Results of PBT and vPvB assessment

#### **General information**

There are no data available on the mixture itself.

#### Results of PBT and vPvB assessment

The product contains no PBT substances The product contains no vPvB substances.

#### **12.6 Endocrine disrupting properties**

#### Endocrine disrupting properties with respect to the envrionment

The product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms.

#### 12.7. Other adverse effects

**General information** 

Trade name: P 2 1 L

Version: 8 / GB



Date revised: 27.06.2024

Print date: 22.10.2024

Substance number: 3514009700019 Replaces Version: 7 / GB

There are no data available on the mixture itself.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

#### Disposal recommendations for the product

Do not allow to enter drains or water courses.

Wastes and emptied containers should be classified in accordance with relevant national regulation. The European Waste Catalogue classification of this product, when disposed of as waste is EWC waste code 08 03 12\* waste ink containing dangerous substances If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

For further information contact your local waste authority.

#### Disposal recommendations for packaging

Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers.

Empty containers must be scrapped or reconditioned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions.

	Land transport ADR/RID	Marine transport IMDG/GGVSee	Air transport ICAO/IATA
14.1. UN number	1210	1210	1210
14.2. UN proper shipping name	PRINTING INK RELATED MATERIAL	PRINTING INK RELATED MATERIAL	PRINTING INK RELATED MATERIAL
14.3. Transport hazard class(es)	3	3	3
Label			
14.4. Packing group	111	111	111
Limited Quantity	51	51	
Transport category	3		
14.5. Environmental hazards	-		
Tunnel restriction code	D/E		

# **SECTION 14: Transport information**

#### Information for all modes of transport

14.6. Special precautions for user

Transport within the user's premises:

Always transport in closed containers that are upright and secure.

Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Version: 8 / GB

Replaces Version: 7 / GB



Date revised: 27.06.2024

Print date: 22.10.2024

Substance number: 3514009700019

### Other information

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### VOC

VOC (EU)	97,5	%
VOC (EU)	848,3	g/l

#### Other regulations, restrictions and prohibition regulations

The product complies with the requirements of the Persistent Organic Pollutants Regulation 2019/1021. The product complies with the requirements of Regulation 2024/590 on substances that deplete the ozone layer.

The product is not subject to Regulation 649/2012 on the export and import of dangerous chemicals.

#### Other information

The product does not contain substances of very high concern (SVHC).

#### Other information

All components are contained in the AICS inventory.

All components are contained in the DSL inventory.

All components are contained in the IECSC inventory.

All components are contained in the ENCS inventory.

All components are contained in the ECL inventory.

All components are contained in the PICCS inventory.

#### 15.2. Chemical safety assessment

For this preparation a chemical safety assessment has not been carried out.

# **SECTION 16: Other information**


#### Hazard statements listed in Chapter 3

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
	stad in Chanter 2

#### CLP categories listed in Chapter 3

Acute Tox. 4	Acute toxicity, Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1


Safety data sheet in	accordance with regulation	n (EC) No 1907/2006
ourory duta onoor m	accel aanoe mini regalane.	



Substance number: 3514009700019

Version: 8 / GB

Replaces Version: 7 / GB



Print date: 22.10.2024

Eye Irrit. 2	Eye irritation, Category 2
Flam. Liq. 2	Flammable liquid, Category 2
Flam. Liq. 3	Flammable liquid, Category 3
Skin Irrit. 2	Skin irritation, Category 2
STOT RE 2	Specific target organ toxicity - repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

#### Supplemental information

Relevant changes compared with the previous version of the safety data sheet are marked with: \*\*\* This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship. The information in this Safety Data Sheet is based on the present state of knowledge and current legislation.

It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.